

sinopé



Smart Floor Heating Thermostat TH1300WF



Heating cables



Heating cable mats



■ FEATURES

- Backlit display
- Detects the connected load
- Lockable buttons
- Allows floor or ambient temperature control
- Allows control of the ambient temperature taking into account the minimum and maximum temperature limits of the floor
- Allows control of the floor temperature taking into account the maximum ambient temperature limit
- Personalization of the minimum and maximum temperatures available for thermostat control
- Indoor (according to the control mode), outdoor, and setpoint temperatures featured on the thermostat display
- Temperature displayed in °C or °F

This thermostat is equipped with:

- Floor sensor output
- Auxiliary heating system output
- Protection for engineered wood flooring
- Built-in ground fault circuit interrupter (Class A GFCI)

■ COMMUNICATION

Protocol: Wi-Fi

Standard: IEEE 802.11 b/g/n

Frequency: 2.4 GHz

■ ACCESSORIES



Expansion Unit TR1310

For any installation exceeding 15 A, use the expansion unit in addition to the thermostat.



Floor Sensor AC1310-01

Complete your installation like a pro by adding a 2nd sensor during installation.



- **Scenes:** activate personalized ambiances according to the time of the day, events or activity
- **Schedules:** set a different schedule for each day of the week, up to 8 periods per day
- **Energy reports:** see your consumption and savings in real-time
- **Geofencing:** trigger actions based on your presence
- **Voice assistants:** works with Amazon Alexa and Google Assistant

* Discover more features: sinopetech.com

■ TECHNICAL SPECIFICATIONS

Operating voltage: 120/208/240 Vac, 50/60 Hz

Maximum load:

1800 W @ 120 V / 15 A

3120 W @ 208 V / 15 A

3600 W @ 240 V / 15 A

Setpoint range: 5 °C to 36 °C [41 °F to 97 °F]

Display range: 0 °C to 70 °C [32 °F to 99 °F]

Storage: -20 °C to 50 °C [-4 °F to 122 °F]

Resolution: ± 0.5 °C (± 1 °F)

Auxiliary output:

24 Vac / Vdc / 0.1 A

Compatibility: 10K Ω / 12K Ω sensors at 25 °C

Floor sensor included

3-year warranty


■ CERTIFICATION



■ STANDARDS

TB713-C Base: Conforms to ANSI/UL Std. 943

Certified under CAN/CSA Std. C22.2 No. 144.1



sinopé

T: 450.741.7700

TF: 1.855.741.7701

sinopetech.com - sales@sinopetech.com

Saint-Jean-sur-Richelieu, Qc, Canada