

sinopé



Smart Double-Pole Thermostat TH1500ZB



Electric baseboard



Fan-forced convector



Convector



Radiant ceiling heating



■ FEATURES*

- Backlit display
- Detects the connected load
- Lockable buttons
- Personalization of the minimum and maximum temperatures available for thermostat control
- Indoor and outdoor temperatures featured on the thermostat display
- Temperature displayed in °C or °F

* These features are available in Neviweb and require the GTI30 hub. Features may vary from a platform to another.



- **Automations:** create automations that run based on time, sunrise/sunset, device action, or your presence
- **Scenes:** activate personalized ambiances according to the time of the day, events or activity
- **Energy reports:** see your consumption and savings in real-time
- **Geofencing:** trigger actions based on your presence
- **Voice assistants:** works with Amazon Alexa and Google Assistant

* Discover more features: sinopetech.com

■ COMMUNICATION

Protocol: Zigbee 3.0
Frequency: 2.4 GHz
Transmission power: +20 dBm
Receiver sensitivity: -108 dBm
Encryption key: AES-128

■ CERTIFICATION



■ STANDARDS

Conforms to CSA-C828-13

■ TECHNICAL SPECIFICATIONS

Operating voltage: 120/208/240/277 Vac, 50/60 Hz

Relay switching

Maximum load:

1800 W @ 120 Vac / 15 A

3120 W @ 208 Vac / 15 A

3600 W @ 240 Vac / 15 A

4155 W @ 277 Vac / 15 A


Setpoint range: 5 °C to 36 °C [41 °F to 97 °F]

Display range: 0 °C to 50 °C [32 °F to 99 °F]

Storage: -20 °C to 50 °C [-4 °F to 122 °F]

Resolution: ± 0.5 °C [± 1 °F]

3-year warranty



sinopé

T: 450.741.7700
TF: 1.855.741.7701

sinopetech.com - sales@sinopetech.com
Saint-Jean-sur-Richelieu, Qc, Canada

Neviweb is a trademark of Sinopé Technologies Inc., registered in Canada and the U.S.
Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates.
Google is a trademark of Google LLC.