

Smart Light Switch

SW2500ZB-C4

Light-emitting diode (LED)

Incandescent lighting

Compact fluorescent lamp (CFL)

Resistive load

Halogen lighting Ceiling fan



■ FEATURES*

- Remotely operate individual lights or groups of lights**
- Personalization of the color and intensity of the LED on the product
- · Ideal for ceiling fans and outdoor lighting
- *Some features must be programmed by a Control4 integrator.
- **Requires a permanent Internet connection and a Control4 controller.

COMMUNICATION

Protocol: Zigbee 3.0 Frequency: 2.4 GHz

Transmission power: +20 dBm Receiver sensitivity: -108 dBm Encryption key: AES-128





STANDARDS

Conforms to ANSI/UL Std.916 Certified under CAN/CSA Std. C22.2 No205

- Integrates with personalized scenes
- Schedule programming
- Voice control with Amazon Alexa and Google Assistant

■ TECHNICAL SPECIFICATIONS

Operating voltage: 120 Vac, 60 Hz

Maximum load:

450 W: LED, compact fluorescent lamp (CFL) and halogen

600 W: Incandescent 1800 W: Resistive ½ HP: Ceiling fan

Operating temperature: 0 °C to 40 °C (32 °F to 104 °F) Storage temperature: -20 °C to 50 °C (-4 °F to 122 °F)

Neutral wire required Simple installation (3 or 4 wires) Single pole, 3-way compatible Wall plate not included 3-year warranty

